





Protection classification

Design
Protection classification
Pneumatic chain hoist model CPA ATEX 1-13 up to 10-9
Pneumatic chain hoist model CPA ATEX 20-8 up to 100-3
Hand chain hoist model Yalelift 360 ATEX
Hand chain hoist with integrated push or geared type trolley model Yalelift 360 IT ATEX
Hand chain hoist with integrated push or geared type trolley (low headroom) model Yalelift 360 LH ATEX
Push and geared trolley model HTP/G ATEX
Ratchet lever hoist model UNOplus ATEX
Electric winch model BETA-EX
Sheave block for rope guidance model DSRBX S
Hand winch model OMEGA-EX
Rack and pinion jack model ZWW-EX
Hand pallet truck, stainless steel version model HU 20-115 VATP ATEX PROLINE
STEERMAN model SX ATEX

	BASIC	MEDIUM	HIGH	SPECIAL
	 II 3 GD c IIB T4/ II 2 GD c IIA T4	 II 2 GD c (de) (ck) IIB T4	 II 2 GD c IIC T4	 I M2 only for mining
	only II 3 GD c IIB T4	on request (see hint page 442)		
	X	X	X	
	X	X	X	
	X	X	X	
	X	X	X	
	X		X	
	only II 3 GD c IIB T4			X
		X (de)		
		X		
		X (ck)		
		X		
			II 2 GD c IIC T6	
	II 2 GD c IIB T4			



INFO

Due to the use of stainless steel load chains for the HIGH design a reduction of the load capacity is necessary. Please see the table "technical data" for the appropriate values.

BASIC

- Load chain galvanic zinc-plated, stainless steel hand chain
- Trolleys with buffers
- Brake with cooling element (only for Yalelift range)

MEDIUM

- Load chain galvanic zinc-plated, stainless steel hand chain
- Top and load hook copper-plated
- Trolley equipped with buffers and bronze trolley wheels
- Brake with cooling element (only for Yalelift range)

HIGH

- Stainless steel load and hand chain
- Load and top hook copper-plated
- Trolley equipped with buffers and bronze trolley wheels
- Brake with cooling element (only for Yalelift range)
- Conductive load rollers (only hand pallet truck)

SPECIAL

- Only for mining industry